



VP-4 1:4 VGA Distribution Amplifier



The Kramer **VP-4** is a newly updated, high performance 1:4 distribution amplifier designed to accept a single VGA, SVGA, XGA, etc., source and distribute it to four identical outputs using female 15pin HD connectors. Bandwidth exceeding 350MHz ensures that the **VP-4** remains transparent even at high-resolution VGA modes. The **VP-4** provides AC coupling, as well as buffering and isolation conforming to the highest standards. A 12VDC power supply is included for typical operation, but the model VA-50P is an optional multi-outlet power supply which can run up to six Kramer products requiring 12VDC. The **VP-4** is housed in a rugged, desktop sized enclosure. It can also be mounted in a standard 19" rack using the optional RK-80 which holds two units in one vertical rack spaces.



VP-4

TECHNICAL SPECIFICATIONS

EINGANG:	1 VGA/XGA on an HD 15F connector.
AUSGÄNGE:	4 VGA/XGA on HD 15F connectors.
VIDEOBANDBREITE (- 3 dB):	350 MHz.
DIFFERENZVERSTÄRKUNG:	0.5%.
DIFFERENTIELLE PHASE:	0.1 Deg.
RAUSCHABSTAND:	73dB.
KOPPLUNG:	AC, inputs and outputs, with input protection circuitry.
ABMESSUNGEN:	22cm x 18 cm x 4.5 cm (W, D, H.).
STROMVERSORGUNG:	12VDC, 75 mA, (to be used with a current limited power supply.).
GEWICHT:	1.1 kg. (2.4 lbs.) approx.
ZUBEHÖR:	12VDC power supply.
OPTIONEN:	RK-80 rack mount kit.